



Fluid Grease H1

Elkalub

K-Supply

K-Supply Fluid Grease H1 NLGI N00 is a grease for application in the food industry. The product is adhesive and is suitable for sterilizers, spindles, valves, gears, slow-turning ball bearings, slip motions and for the lubrication of chains.

This product which has been tested and approved at the Komori Graphic Center-Europe shows a good resistance to water (up to 100°C) as well as alkalis and acids.

Benefits

- For application in the food industry.
- Suitable for temperatures from -10°C up to 130°C (short time up to 180°C).

Directions

Storage conditions are 15 - 25°C.


Keep away from sources of ignition.

Suitable packaging; only to be kept in original packaging.

For safety measurements, use hand and eye protection and wear protective clothing.

Specifications

Product name	K-Supply Fluid Grease	
Chemical composition	White oil, synthetic oil, inorganic thickener, additives.	
Classification	KP00K-10	DIN 51 825
Appearance	Brown, transparent grease.	
Upper operating temperature	130°C	
Lowest operating temperature	-10°C	
Short-term operating temperature	180°C	
NLGI-grade	00	DIN 51 818
Base oil viscosity at 40°C	185 mm ² /s	DIN ISO 3448
Water resistance	(0-1)-90	DIN 51 807
Oil separation (K) [%]	< 2	DIN 51 817
Oil separation (N) [%]	< 6	DIN 51 817
Registration no. (H1)	133174	
Packaging	2 Kg Bag 6 x 2 Kg Bag	

 **Directions for Use:**
For details, please refer to the safety data sheet.

KOMORI INTERNATIONAL (EUROPE) B.V.

Reactorweg 151, 3542 AD Utrecht, The Netherlands, Tel: +31 (0)88 177 07 07

www.komori.eu

AJAGAR EN 1P NL 3 2020.09 500 KIE